



Warning

Care should be used to consider that any combination of elements is only as strong as the weakest member of the combined system.

COMPONENTS	Max. Weight Capacity		CLICK RAIL SYSTEM	CABLE SYSTEM	CLASSIC GALLERY SYSTEM	CONTEMPO SYSTEM	TENSIONED CABLE SYSTEM	DISPLAY REVEAL SYSTEM	SPECIALTY HARDWARE
	lb	Kg							
TRACK / ATTACHMENT									
Click Rail Track	120	54	●				●		
Wall Track	300	136		●	●		●		
Ceiling Track	150	68		●	●		●		
Contempo® Track	75	34				●	●		
Pier-to-Pier Articulated	33	15					●		
Pier-to-Pier Fixed	150*	68*					●		
Display Reveal (*per linear foot)	110*	50						●	
VERTICAL COMPONENT									
Barrel-End Cable (stainless steel)	150	68					●		●
Steel Cable (all non-Barrel-End steel/stainless)	45	20	●	●		●	●	●	
Nylon Cord	15	7	●	●		●		●	
Rod - Aluminum	70	35			●	●		●	
Rod - Stainless	110	50			●	●		●	
ROD HOOKS									
B1035 Gallery Classic Hook	110	50			●	●		●	
B1036 Secure Gallery Classic Hook	110	50			●	●		●	
B1037 Stable Gallery Hook	110	50			●	●		●	
CABLE HOOKS									
H3002 Secure-Gripper Hook	40	18	●	●		●	●	●	
H3007 Self-Gripping Hook	33	15	●	●		●	●	●	
H3009 Secure Self-Gripping Hook	33	15	●	●		●	●	●	
H3012 Multi-purpose Hook	15	7	●	●		●	●	●	
H3014 Aluminum Frame Hook	33	15	●	●		●	●	●	
H3018 Mini Hook	12	5.5	●	●		●	●	●	
PANEL FITTINGS									
H3004 Utility Hook	22	10	●	●		●	●	●	
H3005/06/30/31, Panel Hooks (all)	22	10	●	●		●	●	●	
H3040/42 Econo Side Clamps, (all)	2.5	0.9	●	●		●	●	●	
H3050/55 Pro Side Clamp, Sml (both)	20	9	●	●		●	●	●	
H3051/56 Pro Side Clamp, Med (both)	30	13.5	●	●		●	●	●	
H3052/57 Pro Side Clamp, Lrg (both)	40	18	●	●		●	●	●	
H3045/46/47 Top Clamps (all)	150	68					●		●
H3070/71 Top-Bottom Clamps (all)	150	68					●		●
WALL & CEILING HANGERS									
Grid-Ceiling Wall Hanger	5	2							●
Picture Molding Hanger	33	13							●
Panel-Top Hanger	33	13							●

*When installed by fastening into structural wood with the appropriate fastener and the fastener is engaged 1" or more into lumber.

ASHanging.com
866.935.6949

© 2015, 2021 AS Hanging Display Systems
All rights reserved
21E-21

If you have any questions, please call our Customer Service Center at 866-935-6949.